

Liberty Packaging Systems,
21 Mead Park Industrial Estate,
River Way, Harlow, Essex, CM20 2SE

Tel: 01992 460 111

Email: info@libertypackagingsystems.co.uk

Web: www.libertypackagingsystems.co.uk



LIBERTY
PACKAGING SYSTEMS

LPS C7700 SHRINK WRAPPING SYSTEM

Available in
manual or
automatic
versions



Improves presentation and protects of your products

What Does It Do?

The LPS C7700 shrink wrap machine helps to protect products whilst still presenting them in clear, appealing way. The shrink film also protects the products from water damage and strengthens the overall protection of products.

Available in manual or automatic versions. The automatic version has an automatic work cycle (press start for cycles performed in sequence). The manual work cycle performs one packaging cycle when the start button is pressed.

Key Features:

- Ultra Performing heating elements (Reduce shrink time by 50%, heating time by 60%, less energy consumption and increased productivity).
- Sealing bars with closed circuit cooling system and patented safety system (Increased productivity & Optimal sealing)
- Soft Shrink Fan Speed Adjustment (Prevents the seals from opening whilst shrinking, perfect heat-shrink even when light or v flexible products, v low noise, Unique Patent).
- Comfort Zone Fan Stop (No more heat & hot air for operator, 20% energy saving)
- Menu in 8 languages (English, German, French, Spanish, Italian, Portuguese, Czech, Russian)
- Wire product discharge mesh belt
- Innovative upper hood fastening: simplified maintenance and enhanced stability
- Sealing blades safety control: enhanced machine safety
- Support with larger reel diameter (to 300 mm): suitable for micro-punched film to pack bread
- Packaging plate separated from the reel support: suitable to package even very small products with the same film reel
- Larger packaging plate: in a size suitable to the heat-shrink chamber
- Innovative micro-perforator: continuous and optimal perforation
- Boosted fan motor: superior shrinking performance
- Added safety thermostat installed directly on the resistor of the heat chamber: greater safety
- Glue-less neoprene rubber support: easy to replace, does not require the use of glue.

LPS - PACKAGING MADE EASY

SPECIFICATIONS	
Speed	Up to 300 products per hour – Speeds are dependant upon applications and operators.
Maximum Power	5.15kw
Power Supply	200/208/400v
Phase	3ph
Sealing Bar Dimensions	Max 840mm x 590mm
Max Film Roll Dimensions	300mm x 800mm
Working Plate Height	940mm
Machine Weight	215kg
Machine Dimensions with Open Hood	1950mm x 1000mm x 1480mm
Machine Dimensions with Closed Hood	3120mm x 1000mm x 1180mm
Packed machine dimensions	2180mm x 1040mm x 1430mm



OPTIONS	
Stainless steel packaging plate	
Opening Film Blower	
Higher hood 300 mm	
Sheet Metal Film Opener	
High hood 490 mm	
Stainless steel air deflector (2 pcs)	
Larger reel support 1000mm	
Roller conveyor lg. 1 m (with 2 supports)	
Pedal	
Pedal Protection	

Why Choose An LPS Shrink Wrapping System?

Liberty Packaging Systems is one of the UK's leading suppliers of packaging. As well as having a dedicated team of knowledgeable experts to offer advice and bespoke solutions to suit your mailing needs, we have a well-trained customer support team and highly skilled team of field engineers to support you after your purchase.

This reliable and efficient after-care support service is provided to ensure you get the most out of your purchase. We also offer a comprehensive range of technical support and service packages that cover both equipment and software. Our maintenance packages are an economical way to maximise performance and the longevity of your machine, overall resulting in peace of mind.



**Liberty Packaging Systems,
21 Mead Park Industrial Estate,
River Way, Harlow, Essex, CM20 2SE**

**Tel: 01992 460 111 Email: info@libertypackagingsystems.co.uk
Web: www.libertypackagingsystems.co.uk**