

Liberty Packaging Systems,
21 Mead Park Industrial Estate,
River Way, Harlow, Essex, CM20 2SE

Tel: 01992 460 111

Email: info@libertypackagingsystems.co.uk

Web: www.libertypackagingsystems.co.uk



LIBERTY
PACKAGING SYSTEMS

LPS SLEEVE WRAPPER SW900P SEMIAUTOMATIC WITH PUSHER



Improves presentation and protects your products

What Does It Do?

Our sleeve wrapper range is characterised by the great versatility of the models combining efficiency, reliability and high performance. This all guarantees ideal working conditions in any activity the user carries out. The models of the SW range represent the extreme simplification of sleeve wrapper machines. They are built with a solid single-unit structure and are equipped with a safety photocell which blocks the sealing bar whenever it encounters an obstacle in its path.

The SW Sleeve Wrappers wrap both individual or multiple products in polythene / polyethylene film. The model is able to meet any wrapping requirement thanks to the wide range of options. It can wrap products as long as 1500 mm and thanks to the control selector, the operator can choose whether to work in automatic or semiautomatic mode.

Key Features

- Pneumatic pusher in line with scraper
- Hot bar – sealing bar type with film cut by cold blade
- Safety photocell that blocks the sealing bar if it encounters an obstacle in its path
- Automatic upper and lower system to unwind the film reel with dragging rollers
- Heat-shrinking tunnel with air circulation system
- Adjustable speed of the conveyor belt in the tunnel
- Average electricity consumption is reduced by about 40% during normal operation
- Air consumption 150 nl/min
- Pneumatic components that work with non-lubricated dry air
- Switch for manual or semi-automatic operation
- Power supply: Option between 3phases 220V and 400V 3phases + N + E
- Machines compatible with Machinery Directive 2006/42/EC systems and motorised winder system are standard in this machine.

LPS - PACKAGING MADE EASY

SPECIFICATIONS

Speed	Up to 12 products per minute – Speeds are dependant upon applications and operators.
Maximum Power	27kw
Electric consumption	14 kWh
Power Supply	220/400 (3 phase)
Air pressure bar	6
Air consumption per cycle nl	15
Effective sealing bar dimensions	900mm (h) x 380 (w)mm
Max product height	380mm (h)
Max reel dimensions	350mm x 880mm
Worktop height	Standard 850mm+25
Machine dimensions	3600mm x 1500mm x (h) 1980mm
Tunnel infeed dimensions	800mm x400 (h)
Tunnel chamber length	1500mm
Machine weight	1400kg



Why Choose An LPS Shrink Wrapping System?

Liberty Packaging Systems is one of the UK's leading suppliers of mailroom equipment. As well as having a dedicated team of knowledgeable experts to offer advice and bespoke solutions to suit your mailing needs, we have a well-trained customer support team and highly skilled team of field engineers to support you after your purchase.

This reliable and efficient after-care support service is provided to ensure you get the most out of your purchase. We also offer a comprehensive range of technical support and service packages that cover both equipment and software. Our maintenance packages are an economical way to maximise performance and the longevity of your machine, overall resulting in peace of mind.



**Liberty Packaging Systems,
21 Mead Park Industrial Estate,
River Way, Harlow, Essex, CM20 2SE**

**Tel: 01992 460 111 Email: info@libertypackagingsystems.co.uk
Web: www.libertypackagingsystems.co.uk**