



WRAPMATIC 240 WRAPPING SYSTEM



Improves the Security & Presentation of Your Products

What Does It Do?

The Wrapmatic is a completely fully automatic wrapping machine. The L Sealing system provides an all-round centre seal. Fitted with a standard kissing belt and adjustable centre sealing device, the machine can pack single or multiple items. Up to **3,600** items can be wrapped in an hour dependent on film and product size. A **GREAT ADVANTAGE** of this system is that it doesn't require a pneumatic connection and works only with electrical supply. The benefits of this include **REDUCED MAINTENANCE** and **NOISE LEVELS, IMPROVED SPEED, PRODUCTIVITY & SEALING PRECISION**

How Does It Work?

The Wrapmatic 240 uses just one low cost roll of clear or printed poly film up to a maximum thickness of 80 Microns. The system folds the film into a sealed pack. When the process is complete, the pack is ejected automatically or can be used with a shrink tunnel. Products up to **240mm HEIGHT, 600mm LENGTH** and up to **400MM WIDTH** can be wrapped.

Safety

The machine completely closes by a covering, including the in-feed, out-feed belts and roll support. There are also **SAFETY MICROS** on the access doors of the machine.

Key Features

Complete Automatic
Check at the Start Up

10 Language Touch
Screen Display

Full Waste Film Winder
Alarm Device

Machine on Wheels &
Adjustable Feet

Integrated & Moveable
Film Roll Support

2 Product Reading
Photocells

Visible & Acoustic Alarm
Signal

Anti-Static Belts



Machine Specifications

Speed	Up to 3600 Per Hr – Dependant on application
Material Size	Max 400mm (w) x 600mm (L) x 240mm (h)
Sealing Bar Dimensions	640mm x 500mm
Max Film Roll	300mm x 700mm wide
Wrapping Film Types	PE, HDPE, Polyolefin, Polyethylene and many others including bio-degradable
Wrapping Film Thickness	Up to 80 Microns – Minimum thickness by test
Machine Dimensions (With Closed Hood)	2485mm (l) x 1240mm (d) x 1715mm (h)
Machine Dimensions (With Open Hood)	2485mm (l) x 1240mm (d) x 1900mm (h)
Machine Weight	763/813 kgs
Power	Single Phase 230VAC
Safety	Cover With Interlocking Switch



Centre Sealing



The Shrink tunnel 50 works with the WrapMatic 240



No pneumatic connection needed

Why Choose An LPS System?

As well as having a dedicated team of knowledgeable experts to offer advice and bespoke solutions to suit your mailing needs, we have a well-trained customer support team and highly skilled team of field engineers to support you after your purchase.

This reliable and efficient after-care support service is provided to ensure you get the most out of your purchase. We also offer a comprehensive range of technical support and service packages that cover both equipment and software. Our maintenance packages are an economical way to maximise performance and the longevity of your machine, overall resulting in peace of mind.

