LIBERTY
PACKAGING SYSTEMS

Liberty Packaging Systems,
Unit 21 Mead Park Industrial Estate
River Way, Harlow, Essex, CM20 2SE
Tel: 01992 460 111
Email: info@libertypackagingsystems.co.uk
Web: www.libertypackagingsystems.co.uk

SALA Label Applicator Range

A Selection of Label Applicators for Our Range of Packaging Machines

What Does It Do?

The LPS range of automatic self-adhesive label applicators can be added to most LPS packaging equipment, ideal for application on flat or slightly uneven products. The SALA labeller head can be used for applying labels to the top or sides of products. The main feature of the model is the **SIMPLICITY** of installation and use. The head is available in right or left hand versions.

SALA Label Applicators are available in a number of versions with a range of max label widths – 50mm, 100mm, 140mm, 190mm 230mm and 260mm

Included

Electronic control unit managed by a microprocessor with display, possibility of controlling the delivery speed, start delay, label pre-distribution, piece counter, Start and label reading by photocell. Power supply voltage 220 or 110 V 50/60Hz

Model	SALA050	SALA100
Max / Min Label Width	50mm / 10mm	100mm / 10mm
Max / Min Label Length	500mm / 10mm	500mm / 10mm
Min Internal Reel Diameter	38mm (76 with adapter)	38mm (76 with adapter)
Max External Reel Diameter	300mm	300mm

Optional Extras

Hot/Dry Printing for Batch & Date

1000 Pulses Encoder Control Unit

Control Unit for 60m/min Speed

Reel End Paper Break Optical/Acoustic Alarm

Pre Reel End Alarm

Support Column with Base

Self-Locking Wheels

Special Photocell for Transparent Labels